

Development Application – Consent conditions



Folder /DA No:	DA/258/2018
PROPERTY:	5 Crana Avenue, South Coogee
Recommendation:	Approval

1. DEVELOPMENT CONSENT CONDITIONS

GENERAL CONDITIONS

The development must be carried out in accordance with the following conditions of consent.

These conditions have been applied to satisfy the relevant requirements of the *Environmental Planning & Assessment Act 1979*, *Environmental Planning & Assessment Regulation 2000* and to provide reasonable levels of environmental amenity.

Approved Plans & Supporting Documentation

1. The development must be implemented substantially in accordance with the plans and supporting documentation listed below and endorsed with Council’s approved stamp, except where amended by Council in red and/or by other conditions of this consent:

Plan	Drawn by	Dated
Lower Ground Floor Plan	Madeleine Blanchfield Architects	Oct 2018
Ground Floor Plan	Madeleine Blanchfield Architects	Oct 2018
First Floor Plan	Madeleine Blanchfield Architects	Oct 2018
Roof Plan	Madeleine Blanchfield Architects	Oct 2018
West & East Elevation	Madeleine Blanchfield Architects	Oct 2018
North & South Elevation	Madeleine Blanchfield Architects	Oct 2018
Section A & B	Madeleine Blanchfield Architects	Oct 2018

BASIX Certificate No.	Dated
A307320	30/04/18

Amendment of Plans & Documentation

2. The approved plans and documents must be amended in accordance with the following requirements:
 - a. The concrete beam (CNC) on the street elevation that extends from the garage over the pedestrian entrance gate to the southern boundary fence shall be deleted.
 - b. The proposed garage roof landscaping shall be deleted and the roof shall be constructed of lightweight materials (ie. metal roof).
 - c. The overall width of the garage shall be reduced by providing a minimum setback of 900mm from the northern side boundary for the entire northern garage wall.
 - d. The overall height of the proposed garage shall be reduced to a maximum of 2.8m measured above the garage level of RL 23.47 thus allowing for 2.2m height clearance and a 600mm parapet wall or bulkhead above the garage entry.

- e. The garage door shall be recessed at least by 200mm behind the alignment of the garage wall.
- f. The fence and gate on the street boundary shall not exceed 1.8m in height with the upper two thirds of the fence to be at least 30% open when viewed from the street. The gate will need to be at least 30% open when viewed from the street.
- g. The southern boundary wall shall be reduced in height to a maximum of 1.8m (measured above the existing ground levels of the subject site).
- h. Window W.G03 on the southern elevation shall be provided with fixed obscured glazing below 1.6m (measured above the floor level).

REQUIREMENTS BEFORE A CONSTRUCTION CERTIFICATE CAN BE ISSUED

The following conditions of consent must be complied with before a 'Construction Certificate' is issued by either Randwick City Council or an Accredited Certifier. All necessary information to demonstrate compliance with the following conditions of consent must be included in the documentation for the construction certificate.

These conditions have been applied to satisfy the relevant requirements of the *Environmental Planning & Assessment Act 1979*, *Environmental Planning & Assessment Regulation 2000*, Council's development consent conditions and to achieve reasonable levels of environmental amenity.

Consent Requirements

- 3. The requirements and amendments detailed in the 'General Conditions' must be complied with and be included in the construction certificate plans and associated documentation.

External Colours, Materials & Finishes

- 4. The colours, materials and finishes of the external surfaces to the building are to be compatible with the adjacent development to maintain the integrity and amenity of the building and the streetscape.

Details of the proposed colours, materials and textures (i.e. a schedule and brochure/s or sample board) are to be submitted to and approved by Council's Manager Development Assessments prior to issuing a construction certificate for the development.

Section 7.12 Development Contributions

- 5. In accordance with Council's Development Contributions Plan effective from 21 April 2015, based on the development cost of \$863,940 the following applicable monetary levy must be paid to Council: \$8,639.40.

The levy must be paid in **cash, bank cheque** or by **credit card** prior to a construction certificate being issued for the proposed development. The development is subject to an index to reflect quarterly variations in the Consumer Price Index (CPI) from the date of Council's determination to the date of payment. Please contact Council on telephone 9093 6999 or 1300 722 542 for the indexed contribution amount prior to payment.

To calculate the indexed levy, the following formula must be used:

$$\mathbf{IDC = ODC \times CP2/CP1}$$

Where:

IDC = the indexed development cost

ODC = the original development cost determined by the Council

CP2 = the Consumer Price Index, All Groups, Sydney, as published by the ABS in respect of the quarter ending immediately prior to the date of payment

CP1 = the Consumer Price Index, All Groups, Sydney as published by the ABS in respect of the quarter ending immediately prior to the date of imposition of the condition requiring payment of the levy.

Council's Section 94A Development Contribution Plans may be inspected at the Customer Service Centre, Administrative Centre, 30 Frances Street, Randwick or at www.randwick.nsw.gov.au.

Compliance Fee

6. A development compliance and enforcement fee of \$863.95 shall be paid to Council in accordance with Council's adopted Fees & Charges Pricing Policy, prior to the issue of a Construction Certificate for development.

Long Service Levy Payments

7. The required Long Service Levy payment, under the *Building and Construction Industry Long Service Payments Act 1986*, must be forwarded to the Long Service Levy Corporation or the Council, in accordance with Section 109F of the *Environmental Planning & Assessment Act 1979*.

At the time of this development consent, Long Service Levy payment is applicable on building work having a value of \$25,000 or more, at the rate of 0.35% of the cost of the works.

Security Deposit

8. The following damage / civil works security deposit requirement must be complied with as security for making good any damage caused to the roadway, footway, verge or any public place; and as security for completing any public work; and for remedying any defect on such public works, in accordance with section 80A(6) of the *Environmental Planning and Assessment Act 1979*:

- \$3000.00 - Damage / Civil Works Security Deposit

The damage/civil works security deposit may be provided by way of a cash, cheque or credit card payment and is refundable upon a satisfactory inspection by Council upon the completion of the civil works which confirms that there has been no damage to Council's infrastructure.

The owner/builder is also requested to advise Council in writing and/or photographs of any signs of existing damage to the Council roadway, footway, or verge prior to the commencement of any building/demolition works.

To obtain a refund of relevant deposits, a *Security Deposit Refund Form* is to be forwarded to Council's Director of City Services upon issuing of an occupation certificate or completion of the civil works.

Design Alignment levels

9. The design alignment level (the finished level of concrete, paving or the like) at the property boundary for driveways, access ramps and pathways or the like, shall be:

- **50mm above the top of the existing kerb level at all points opposite, along the full site frontage.**

The design alignment levels at the property boundary as issued by Council and their relationship to the kerb must be indicated on the building plans for the construction certificate (a construction note on the plans is considered satisfactory). The design alignment level at the street boundary, as issued by the Council, must be strictly adhered to.

Any enquiries regarding this matter should be directed to Council's Development Engineer on 9093-6881.

10. The above alignment levels and the site inspection by Council's Development Engineer have been issued at a prescribed fee of \$171.00 (inclusive of GST). This amount is to be paid prior to a construction certificate being issued for the development.

Vehicle Access and Garage Design

11. The gradient of the garage floor level must be designed and constructed in accordance with AS 2890.1 (2004) – Off Street Car Parking and the levels of the garage must match the alignment levels at the property boundary (as specified by Council above). Details of compliance are to be included in the construction certificate documentation. A copy of the plans/sections shall be forwarded to Council’s Development Engineers.

NOTES: Internal transitional grading between the Council issued alignment levels and the garage slab level may be permitted up to a maximum of 1 in 8 (12.5%) provided it is restricted to within 1.5m of the Crana Avenue property alignment.

The PCA must be satisfied that satisfactory vehicle access can be achieved in accordance with the above requirements prior to the issuing of a construction certificate.

Sydney Water

12. All building, plumbing and drainage work must be carried out in accordance with the requirements of the Sydney Water Corporation.

The approved plans must be submitted to the Sydney Water **Tap in™** online service, to determine whether the development will affect Sydney Water’s waste water and water mains, stormwater drains and/or easements, and if any further requirements need to be met.

The **Tap in™** service provides 24/7 access to a range of services, including:

- Building plan approvals
- Connection and disconnection approvals
- Diagrams
- Trade waste approvals
- Pressure information
- Water meter installations
- Pressure boosting and pump approvals
- Change to an existing service or asset, e.g. relocating or moving an asset.

Sydney Water’s **Tap in™** online service is available at:
<https://www.sydneywater.com.au/tapin>

The Principal Certifying Authority must ensure that the developer/owner has submitted the approved plans to Sydney Water Tap in online service.

Stormwater Drainage

13. The current method of stormwater disposal on the site does not comply with Council’s current requirements and shall be upgraded as part of the works. Detailed drainage plans with levels reduced to Australian Height Datum (AHD), shall be prepared by a suitably qualified Hydraulic Engineer and be submitted to and approved by the certifying authority. A copy of the plans shall be forwarded to Council, if Council is not the certifying authority.

The drainage plans must demonstrate compliance with the Building Code of Australia, Australian Standard AS3500.3:2003 (Plumbing and Drainage - Stormwater Drainage) and the relevant conditions of this development approval.

14. Stormwater runoff from the redeveloped site shall be discharged either:
- a. To the kerb and gutter along the site frontage by gravity (a charged or pump-out system is permitted); OR
 - b. Through a private drainage easement(s) to Council’s kerb and gutter (or underground drainage system); OR

- c. Through a private drainage easement(s) to Council's coastal reserve subject to further approval of concept design by Council's Development Engineer and Bushland Supervisor.
 - d. To a suitably sized infiltration area (subject to a geotechnical investigation confirming the site conditions are suitable for infiltration (e.g. no rock))
15. Should a charged system be required to drain any portion of the site, the charged system must be designed such that;
- i. There are suitable clear-outs/inspection points at pipe bends and junctions.
 - ii. The maximum depth of the charged line does not exceed 1m below the gutter outlet.
16. Should a pump system be required to drain any portion of the site the system must be designed with a minimum of two pumps being installed, connected in parallel (with each pump capable of discharging at the required discharge rate) and connected to a control board so that each pump will operate alternatively. The pump wet well shall be sized for the 1 in 100 year, 2 hour storm assuming both pumps are not working.

The pump system must also be designed and installed strictly in accordance with Randwick City Council's Stormwater Code.

17. All pump out water must pass through a stilling pit, located within the site, prior to being discharged by gravity to the kerb and gutter on Crana Avenue.
18. Should stormwater be proposed to be discharged to an infiltration area the infiltration area shall be sized based on a minimum requirement of 1 m² of infiltration area (together with 1 m³ of storage volume) for every 20 m² of roof/impervious area on the site.

Infiltration areas must be located a minimum of 3.0 metres from any structure (note: this set back requirement may not be necessary if a structural engineer or other suitably qualified person certifies that the infiltration area will not adversely affect the structure) and 2.1 metres from any adjacent side or rear boundary.

Prior to the use of infiltration, a geotechnical investigation will be required to determine whether the ground is suitable for infiltration. Should rock and/or a water table be encountered within two metres of the proposed base of the infiltration pit, or the ground conditions comprise low permeability soils, infiltration will not be appropriate.

19. Should stormwater be proposed to be discharged to the coastal reserve by private drainage easement the location of discharge pipe is to be approved by Council's Development Engineer and Bushland Supervisor prior to a construction certificate being issued for this development. Drainage Plans shall indicate suitable scour protection and the discharge point shall be as discreet as much as possible.

Landscaping

20. The Certifying Authority/PCA must ensure that the Landscape Plan submitted as part of the approved Construction Certificate is substantially consistent with the Landscape Plan by Sticks & Stones Landscape Design, dwg C102, dated 24.10.18, with the Roof Top planting to also be consistent with the Details by FytoGreen, dwg's 36/1 - 9, dated 05.05.16.

REQUIREMENTS TO BE INCLUDED IN THE CONSTRUCTION CERTIFICATE

The requirements contained in the following conditions of consent must be complied with and details of compliance must be included in the construction certificate for the development.

These conditions have been applied to satisfy the relevant requirements of the *Environmental Planning & Assessment Act 1979*, *Environmental Planning & Assessment Regulation 2000*, Councils development consent conditions and to achieve reasonable levels of environmental amenity.

Compliance with the Building Code of Australia

21. In accordance with section 80 A (11) of the *Environmental Planning & Assessment Act 1979* and clause 98 of the *Environmental Planning & Assessment Regulation 2000*, it is a *prescribed condition* that all building work must be carried out in accordance with the provisions of the Building Code of Australia (BCA). Details of compliance with the BCA are to be included in the construction certificate application.

BASIX Requirements

22. In accordance with section 80A(11) of the *Environmental Planning & Assessment Act 1979* and clause 97A of the *Environmental Planning & Assessment Regulation 2000*, the requirements and commitments contained in the relevant BASIX Certificate must be complied with.

The required commitments listed and identified in the BASIX Certificate must be included on the construction certificate plans, specifications and associated documentation, to the satisfaction of the Certifying Authority.

The design of the building must not be inconsistent with the development consent and any proposed variations to the building to achieve the BASIX commitments may necessitate a new development consent or amendment to the existing consent to be obtained, prior to a construction certificate being issued.

Stormwater Drainage

23. A surface water/stormwater drainage system must be provided in accordance with the following requirements, to the satisfaction of the Certifying Authority and details are to be included in the construction certificate:-

- a) Surface water/stormwater drainage systems must be provided in accordance with the relevant provisions of the Building Code of Australia (Volume 2) and relevant Standards;
- b) The surface water/stormwater must be drained and discharged to the street gutter or, subject to site suitability, the stormwater may be drained to a suitably designed absorption pit;
- c) Any absorption pits or soaker wells should be located not less than 3m from any adjoining premises and the stormwater must not be directed to any adjoining premises or cause a nuisance;
- d) External paths and ground surfaces are to be constructed at appropriate levels and be graded and drained away from the building and adjoining premises, so as not to result in the entry of water into the building, or cause a nuisance or damage to the adjoining premises;
- e) Details of any proposed drainage systems or works to be carried out in the road, footpath or nature strip must be submitted to and approved by Council before commencing these works;
- f) A certificate, from a suitably qualified person must be submitted to the PCA and Council, prior to the issue of an Occupation Certificate, which confirms that the stormwater drainage system has been provided in accordance with the requirements of this consent, relevant standards and requirements.

REQUIREMENTS PRIOR TO THE COMMENCEMENT OF ANY WORKS

The following conditions of consent must be complied with prior to the commencement of any works on the site. The necessary documentation and information must be provided to the Council or the 'Principal Certifying Authority' (PCA), as applicable.

These conditions have been applied to satisfy the relevant requirements of the *Environmental Planning & Assessment Act 1979*, *Environmental Planning & Assessment Regulation 2000* and to provide reasonable levels of public health, safety and environmental amenity.

Certification, PCA & other Requirements

24. Prior to the commencement of any building works, the following requirements must be complied with:

- a) a *Construction Certificate* must be obtained from the Council or an accredited certifier, in accordance with the provisions of the *Environmental Planning & Assessment Act 1979*.

A copy of the construction certificate, the approved development consent plans and consent conditions must be kept on the site at all times and be made available to the Council officers and all building contractors for assessment.

- b) a *Principal Certifying Authority* (PCA) must be appointed to carry out the necessary building inspections and to issue an *occupation certificate*; and
- c) a *principal contractor* must be appointed for the building work, or in relation to residential building work, an *owner-builder* permit may be obtained in accordance with the requirements of the *Home Building Act 1989*, and the PCA and Council are to be notified accordingly; and
- d) the *principal contractor* must be advised of the required *critical stage inspections* and other inspections to be carried out, as specified by the *Principal Certifying Authority*; and
- e) at least two days notice must be given to the Council, in writing, prior to commencing any works.

Home Building Act 1989

25. In accordance with section 80 A (11) of the *Environmental Planning & Assessment Act 1979* and clause 98 of the *Environmental Planning & Assessment Regulation 2000*, the requirements of the *Home Building Act 1989* must be complied with.

Details of the Licensed Building Contractor and a copy of the relevant Certificate of Home Warranty Insurance or a copy of the Owner-Builder Permit (as applicable) must be provided to the Principal Certifying Authority and Council.

Dilapidation Reports

26. A dilapidation report must be obtained from a Professional Engineer, Building Surveyor or other suitably qualified independent person, in the following cases:

- excavations for new dwellings, additions to dwellings, swimming pools or other substantial structures which are proposed to be located within the *zone of influence* of the footings of any dwelling, associated garage or other substantial structure located upon an adjoining premises;
- new dwellings or additions to dwellings sited up to shared property boundaries (e.g. additions to a semi-detached dwelling or terraced dwellings);
- excavations for new dwellings, additions to dwellings, swimming pools or other substantial structures which are within rock and may result in vibration and or potential damage to any dwelling, associated garage or other substantial structure located upon an adjoining premises;

- as otherwise may be required by the *Principal Certifying Authority*.

The dilapidation report shall include details of the current condition and status of any dwelling, associated garage or other substantial structure located upon the adjoining premises and shall include relevant photographs of the structures, to the satisfaction of the *Principal Certifying Authority*.

The dilapidation report must be submitted to the Council, the *Principal Certifying Authority* and the owners of the adjoining/nearby premises encompassed in the report, prior to commencing any site works (including any demolition work, excavation work or building work).

Construction Noise & Vibration Management Plan

27. Noise and vibration emissions during the construction of the building and associated site works must not result in damage to nearby premises or result in an unreasonable loss of amenity to nearby residents and the relevant requirements of the *Protection of the Environment Operations Act 1997* and NSW EPA Guidelines must be satisfied at all times.

Noise and vibration from any rock excavation machinery, pile drivers and all plant and equipment must be minimised, by using appropriate plant and equipment, silencers and the implementation of noise management strategies.

A *Construction Noise Management Plan*, prepared in accordance with the NSW EPA Construction Noise Guideline by a suitably qualified person, is to be implemented throughout the works, to the satisfaction of the Council. A copy of the strategy must be provided to the Principal Certifying Authority and Council prior to the commencement of works on site.

Construction Site Management Plan

28. A *Construction Site Management Plan* must be developed and implemented prior to the commencement of any works. The construction site management plan must include the following measures, as applicable to the type of development:

- location and construction of protective fencing / hoardings to the perimeter of the site;
- location of site storage areas/sheds/equipment;
- location of building materials for construction;
- provisions for public safety;
- dust control measures;
- site access location and construction
- details of methods of disposal of demolition materials;
- protective measures for tree preservation;
- provisions for temporary sanitary facilities;
- location and size of waste containers/bulk bins;
- details of proposed sediment and erosion control measures;
- provisions for temporary stormwater drainage;
- construction noise and vibration management;
- construction traffic management details.

The site management measures must be implemented prior to the commencement of any site works and be maintained throughout the works, to the satisfaction of Council.

A copy of the Construction Site Management Plan must be provided to the Principal Certifying Authority and Council prior to commencing site works. A copy must also be maintained on site and be made available to Council officers upon request.

Demolition Work

29. Demolition Work must be carried out in accordance with Australian Standard AS2601-2001, Demolition of Structures and relevant work health and safety requirements.

A Demolition Work Plan must be prepared for the demolition works which should be submitted to the Principal Certifying Authority (PCA), not less than two (2) working days before commencing any demolition work. A copy of the Demolition Work Plan must be maintained on site and be made available to Council officers upon request.

If the work involves asbestos products or materials, a copy of the Demolition Work Plan must also be provided to Council not less than 2 days before commencing those works.

Demolition & Construction Waste

30. A *Demolition and Construction Waste Management Plan* (WMP) must be developed and implemented for the development, to the satisfaction of Council.

The Waste Management Plan must provide details of the type and quantities of demolition and construction waste materials, proposed re-use and recycling of materials, methods of disposal and details of recycling outlets and land fill sites.

Where practicable waste materials must be re-used or recycled, rather than disposed and further details of Council's requirements including relevant guidelines and pro-forma WMP forms can be obtained from Council's Customer Service Centre or by telephoning Council on 9399 0999.

Details and receipts verifying the recycling and disposal of materials must be kept on site at all times and presented to Council officers upon request.

Public Utilities

31. A *Public Utility Impact Assessment* must be carried out on all public utility services on the site, roadway, nature strip, footpath, public reserve or any public areas associated with and/or adjacent to the development/building works and include relevant information from public utility authorities and exploratory trenching or pot-holing, if necessary, to determine the position and level of service.
32. The applicant must meet the full cost for telecommunication companies, gas providers, Ausgrid, and Sydney Water to adjust/repair/relocate their services as required. The applicant must make the necessary arrangements with the service authority.

NOTE: The existing overhead power feed between the mains distribution pole in Crana Avenue and the development site shall remain or be relocated to an underground (UGOH) connection. No permanent private poles are to be installed. The applicant/owner is to liaise with an Ausgrid Accredited Service Provider to carry out any required works to the requirements and satisfaction of Ausgrid and at no cost to Council.

REQUIREMENTS DURING CONSTRUCTION & SITE WORK

The following conditions of consent must be complied with during the demolition, excavation and construction of the development.

These conditions have been applied to satisfy the relevant requirements of the *Environmental Planning & Assessment Act 1979*, *Environmental Planning & Assessment Regulation 2000* and to provide reasonable levels of public health, safety and environmental amenity during construction.

Inspections During Construction

33. Building works are required to be inspected by the *Principal Certifying Authority*, in accordance with sections 109 E (3) of the *Environmental Planning & Assessment Act 1979* and clause 162A of the *Environmental Planning & Assessment Regulation 2000*, to monitor compliance with the relevant standards of construction, Council's development consent and the construction certificate.

Site Signage

34. A sign must be erected and maintained in a prominent position on the site for the duration of the works, which contains the following details:
- name, address, contractor licence number and telephone number of the *principal contractor*, including a telephone number at which the person may be contacted outside working hours, or *owner-builder* permit details (as applicable)
 - name, address and telephone number of the *Principal Certifying Authority*,
 - a statement stating that "unauthorised entry to the work site is prohibited".

Restriction on Working Hours

35. Building, demolition and associated site works must be carried out in accordance with the following requirements:

Activity	Permitted working hours
All building, demolition and site work, including site deliveries (except as detailed below)	<ul style="list-style-type: none"> • Monday to Friday - 7.00am to 5.00pm • Saturday - 8.00am to 5.00pm • Sunday & public holidays - No work permitted
Excavating or sawing of rock, use of jack-hammers, pile-drivers, vibratory rollers/compactors or the like	<ul style="list-style-type: none"> • Monday to Friday - 8.00am to 5.00pm • Saturday - No work permitted • Sunday & public holidays - No work permitted

An application to vary the abovementioned hours may be submitted to Council's Manager Health, Building & Regulatory Services for consideration and approval to vary the specified hours may be granted in exceptional circumstances and for limited occasions (e.g. for public safety, traffic management or road safety reasons). Any applications are to be made on the standard application form and include payment of the relevant fees and supporting information. Applications must be made at least 10 days prior to the date of the proposed work and the prior written approval of Council must be obtained to vary the standard permitted working hours.

Removal of Asbestos Materials

36. Work involving the demolition, storage or disposal of asbestos products and materials must be carried out in accordance with the following requirements:
- Relevant Occupational Health & Safety legislation and WorkCover NSW requirements
 - Randwick City Council's Asbestos Policy
 - A WorkCover licensed demolition or asbestos removal contractor must undertake removal of more than 10m² of bonded asbestos (or as otherwise specified by WorkCover or relevant legislation). Removal of friable asbestos material must only be undertaken by contractor that holds a current friable asbestos removal licence. A copy of the relevant licence must be provided to the Principal Certifying Authority.
 - On sites involving the removal of asbestos, a sign must be clearly displayed in a prominent visible position at the front of the site, containing the words 'DANGER ASBESTOS REMOVAL IN PROGRESS' and include details of the licensed contractor.
 - Asbestos waste must be stored, transported and disposed of in compliance with the *Protection of the Environment Operations Act 1997* and the *Protection of the Environment Operations (Waste) Regulation 2005*. Details of the landfill site (which must be lawfully able to receive asbestos materials) must be provided to the Principal Certifying Authority.

- A Clearance Certificate or Statement, prepared by a suitably qualified person (i.e. an occupational hygienist, licensed asbestos assessor or other competent person), must be provided to Council and the Principal certifying authority upon completion of the asbestos related works which confirms that the asbestos material have been removed appropriately and the relevant conditions of consent have been satisfied.

A copy of Council's Asbestos Policy is available on Council's web site or a copy can be obtained from Council's Customer Service Centre.

Sediment & Erosion Control

37. Sediment and erosion control measures, must be implemented throughout the site works in accordance with the manual for Managing Urban Stormwater – Soils and Construction, published by Landcom.

Details of the sediment and erosion control measures to be implemented on the site must be included in with the *Construction Management Plan* and be provided to the Principal Certifying Authority and Council. A copy must also be maintained on site and be made available to Council officers upon request.

Public Safety & Site Management

38. Public safety and convenience must be maintained at all times during demolition, excavation and construction works and the following requirements must be complied with:

- a) Public access to the building site and materials must be restricted by existing boundary fencing or temporary site fencing having a minimum height of 1.5m, to Council's satisfaction.

Temporary site fences are required to be constructed of cyclone wire fencing material and be structurally adequate, safe and constructed in a professional manner. The use of poor quality materials or steel reinforcement mesh as fencing is not permissible.

- b) Building materials, sand, soil, waste materials, construction equipment or other articles must not be placed upon the footpath, roadway or nature strip at any time.
- c) The road, footpath, vehicular crossing and nature strip must be maintained in a good, safe, clean condition and free from any excavations, obstructions, trip hazards, goods, materials, soils or debris at all times. Any damage caused to the road, footway, vehicular crossing, nature strip or any public place must be repaired immediately, to the satisfaction of Council.
- d) All building and site activities (including storage or placement of materials or waste and concrete mixing/pouring/pumping activities) must not cause or be likely to cause 'pollution' of any waters, including any stormwater drainage systems, street gutters or roadways.

Note: It is an offence under the Protection of the Environment Operations Act 1997 to cause or be likely to cause 'pollution of waters', which may result in significant penalties and fines.

Access gates and doorways within site fencing, hoardings and temporary site buildings or amenities must not open out into the road or footway.

- e) Site fencing, building materials, bulk bins/waste containers and other articles must not be located upon the footpath, roadway or nature strip at any time without the prior written approval of the Council.
- f) Adequate provisions must be made to ensure pedestrian safety and traffic flow during the site works and traffic control measures are to be implemented in

accordance with the relevant provisions of the Roads and Traffic Manual "Traffic Control at Work Sites" (Version 4), to the satisfaction of Council.

- g) A Road / Asset Opening Permit must be obtained from Council prior to carrying out any works within or upon a road, footpath, nature strip or in any public place, in accordance with section 138 of the *Roads Act 1993* and all of the conditions and requirements contained in the Road / Asset Opening Permit must be complied with. Please contact Council's Road/Asset Openings officer on 9093 6691 for further details.
- h) Temporary toilet facilities are to be provided, at or in the vicinity of the work site throughout the course of demolition and construction, to the satisfaction of WorkCover NSW and the toilet facilities must be connected to a public sewer or other sewage management facility approved by Council.

Support of Adjoining Land, Excavations & Retaining Walls

- 39. In accordance with section 80 A (11) of the *Environmental Planning & Assessment Act 1979* and clause 98 E of the *Environmental Planning & Assessment Regulation 2000*, it is a prescribed condition that the adjoining land and buildings located upon the adjoining land must be adequately supported at all times.
- 40. All excavations and backfilling associated with the erection or demolition of a building must be executed safely in accordance with appropriate professional standards and excavations must be properly guarded and supported to prevent them from being dangerous to life, property or buildings.

Retaining walls, shoring or piling must be provided to support land which is excavated in association with the erection or demolition of a building, to prevent the movement of soil and to support the adjacent land and buildings, if the soil conditions require it. Adequate provisions are also to be made for drainage.

Details of proposed retaining walls, shoring, piling or other measures are to be submitted to and approved by the Principal Certifying Authority.

- 41. Prior to undertaking any demolition, excavation or building work in the following circumstances, a report must be obtained from a *professional engineer* which details the methods of support for the dwelling or associated structure on the adjoining land, to the satisfaction of the *Principal Certifying Authority*:
 - when undertaking excavation or building work within the zone of influence of the footings of a dwelling or associated structure that is located on the adjoining land;
 - when undertaking demolition work to a wall of a dwelling that is built to a common or shared boundary (e.g. semi-detached or terrace dwelling);
 - when constructing a wall to a dwelling or associated structure that is located within 900mm of a dwelling located on the adjoining land;
 - as may be required by the *Principal Certifying Authority*.

The demolition, excavation and building work and the provision of support to the dwelling or associated structure on the adjoining land, must also be carried out in accordance with the abovementioned report, to the satisfaction of the *Principal Certifying Authority*.

Survey Requirements

- 42. A Registered Surveyor's check survey certificate or other suitable documentation must be obtained at the following stage/s of construction to demonstrate compliance with the approved setbacks, levels, layout and height of the building to the satisfaction of the Principal Certifying Authority (PCA):
 - prior to construction (pouring of concrete) of the footings or first completed floor slab,
 - upon completion of the building, prior to issuing an occupation certificate,

- as otherwise may be required by the PCA.

The survey documentation must be forwarded to the Principal Certifying Authority and a copy is to be forwarded to the Council, if the Council is not the Principal Certifying Authority for the development.

Building Encroachments

43. There must be no encroachment of any structures or building work onto Council's road reserve, footway, nature strip or public place.

Road / Asset Opening Permit

44. A Road / Asset Opening Permit must be obtained from Council prior to carrying out any works within or upon a road, footpath, nature strip or in any public place, in accordance with section 138 of the Roads Act 1993 and all of the conditions and requirements contained in the Road / Asset Opening Permit must be complied with.

The owner/builder must ensure that all works within or upon the road reserve, footpath, nature strip or other public place are completed to the satisfaction of Council, prior to the issuing of a final occupation certificate for the development.

For further information, please contact Council's Road / Asset Opening Officer on 9093 6691 or 1300 722 542.

Tree Management

45. Approval is granted for the removal of all vegetation throughout the subject site so as to accommodate the new dwelling and associated works as shown, as all have been confirmed as being exempt from the DCP due to a combination of their size, location or being listed as undesirable species, and is subject to full implementation of the approved Landscape Plan:
- All of those throughout the front setback, being the variety of *Syagrus romanzoffianum* (Cocos Palms, T1-3, 6-7, 10, 12-17), *Yucca* (T4, 11), *Magnolia grandiflora* (Bull Bay Magnolia, T5), *Metrosideros excelsa* (NZ Xmas Tree, T8) and *Strelitzia nicholii* (Giant Bird of Paradise, T9);
 - Those in the rear setback, which are all too small for the DCP, including from south to north, a *Phoenix robelleenii* (Dwarf Date Palm), a *Trachycarpus fortunei* (Chinese Windmill Palm, T18) and another Cocos Palm;
 - The small dead/lopped street tree on the Crana Avenue verge, just north of the existing vehicle crossing, wholly at the applicant's cost.

Ausgrid Power Feed Connection

46. Should the existing overhead power feed from the Ausgrid Power Pole in Crana Avenue need to be reconnected to the site during any stage of building works it is to comply with either of the following methods:
- From the power pole directly to the façade of dwelling/s, similar to the existing connection, to the satisfaction of Ausgrid
 - Relocate the existing overhead power feed from the distribution pole in the street to the development site via an underground (UGOH) connection (No Private Pole is permitted). These works are to be to Ausgrid requirements.

Note: A Private Power Pole at the front of the site is not permitted in accordance with Council resolution of May 2014. The applicant is to liaise with an Ausgrid Accredited Service Provider to carry out the works as mentioned above at their own expense.

REQUIREMENTS PRIOR TO THE ISSUE OF AN OCCUPATION CERTIFICATE

The following conditions of consent must be complied with prior to the 'Principal Certifying Authority' issuing an 'Occupation Certificate'.

Note: For the purpose of this consent, any reference to 'occupation certificate' shall also be taken to mean 'interim occupation certificate' unless otherwise stated.

These conditions have been applied to satisfy the relevant requirements of the *Environmental Planning & Assessment Act 1979*, *Environmental Planning & Assessment Regulation 2000*, Council's development consent and to maintain reasonable levels of public health, safety and amenity.

Occupation Certificate Requirements

47. An Occupation Certificate must be obtained from the Principal Certifying Authority prior to any occupation of the building work encompassed in this development consent (including alterations and additions to existing buildings), in accordance with the relevant provisions of the *Environmental Planning & Assessment Act 1979*.

BASIX Requirements

48. In accordance with Clause 154B of the *Environmental Planning & Assessment Regulation 2000*, a Certifying Authority must not issue an Occupation Certificate for this development, unless it is satisfied that each of the required BASIX commitments have been fulfilled.

Relevant documentary evidence of compliance with the BASIX commitments is to be forwarded to the Council upon issuing an Occupation Certificate.

Council's Infrastructure, Vehicular Crossings, street verge

49. The applicant must meet the full cost for a Council approved contractor to:
- a. Re/Construct a concrete vehicular crossing and layback at kerb opposite the vehicular entrance to the site to Council's specifications and requirements.
50. The applicant must meet the full cost for Council or a Council approved contractor to repair/replace any damaged sections of Council's footpath, kerb & gutter, nature strip etc which are due to building works being carried out at the above site. This includes the removal of cement slurry from Council's footpath and roadway.
51. All external civil work to be carried out on Council property (including the installation and repair of roads, footpaths, vehicular crossings, kerb and guttering and drainage works), must be carried out in accordance with Council's "Crossings and Entrances – Contributions Policy" and "Residents' Requests for Special Verge Crossings Policy" and the following requirements:
- a) Details of the proposed civil works to be carried out on Council land must be submitted to Council in a Civil Works Application Form. Council will respond, typically within 4 weeks, with a letter of approval outlining conditions for working on Council land, associated fees and workmanship bonds. Council will also provide details of the approved works including specifications and construction details.
 - b) Works on Council land, must not commence until the written letter of approval has been obtained from Council and heavy construction works within the property are complete. The work must be carried out in accordance with the conditions of development consent, Council's conditions for working on Council land, design details and payment of the fees and bonds outlined in the letter of approval.
 - c) The civil works must be completed in accordance with the above, prior to the issuing of an occupation certificate for the development, or as otherwise approved by Council in writing.

Stormwater Drainage

52. The applicant shall submit to the Principal Certifying Authority (PCA) and Council, certification from a suitably qualified and experienced Hydraulic Engineer confirming that the design and construction of the stormwater drainage system complies with Australian Standard 3500.3:2003 (Plumbing & Drainage- Stormwater Drainage) and the conditions of this development approval. The certification must be provided following inspection/s of the site stormwater drainage system by the certifying engineers and shall be provided to the satisfaction of the PCA.
53. Should a infiltration/pump-out system be provided, a works-as-executed drainage plan prepared by a registered surveyor and approved by a suitably qualified and experienced hydraulic consultant/engineer must be forwarded to the Principal Certifying Authority and the Council. The works-as-executed plan must include the following details (as applicable):
- The location, diameter, gradient and material (i.e. PVC, RC etc) of all stormwater pipes;
 - Details of any infiltration areas.
 - Details of pumping systems installed (including wet well volumes).
54. Should a infiltration/pump-out system be provided, a "restriction on the use of land" and "positive covenant" (under section 88E of the Conveyancing Act 1919) shall be placed on the title of the subject property to ensure that the onsite pump-out system is maintained and that no works which could affect the design function of the pump-out system are undertaken without the prior consent (in writing) from Council. Such restriction and positive covenant shall not be released, varied or modified without the consent of the Council.

Notes:

- a. The "restriction on the use of land" and "positive covenant" are to be to the satisfaction of Council. A copy of Council's standard wording/layout for the restriction and positive covenant may be obtained from Council's Development Engineer.
- b. The works as executed drainage plan and hydraulic certification must be submitted to Council prior to the "restriction on the use of land" and "positive covenant" being executed by Council.

Landscaping

55. Prior to issuing any Final Occupation Certificate, certification from a qualified professional in the landscape/horticultural industry must firstly be submitted to, and be approved by, the PCA, confirming the date that the completed landscaping was inspected, and that it has been installed substantially in accordance with the Landscape Plan by Sticks & Stones Landscape Design, dwg C102, dated 24.10.18, and that the Roof Top planting is also consistent with the Details by FytoGreen, dwg's 36/1 – 9, dated 05.05.16.
56. Suitable strategies shall be implemented to ensure that the landscaping and rooftop planting, drainage layers and similar are all maintained in a healthy and vigorous state until maturity, for the life of the development.
57. That part of the nature-strip upon Council's footway which is damaged during the course of the works shall be re-graded and re-turfed with Kikuyu Turf rolls, including turf underlay, wholly at the applicant's cost, to Council's satisfaction, prior to the issue of any Occupation Certificate

Street and/or Sub-Address Numbering

58. Street numbering must be provided to the front of the premises in a prominent position, in accordance with the Australia Post guidelines and AS/NZS 4819 (2003) to the satisfaction of Council.

If this application results in an additional lot, dwelling or unit, an application must be submitted to and approved by Council's Director of City Planning, together with the required fee, for the allocation of appropriate street and/or unit numbers for the development. The street and/or unit numbers must be allocated prior to the issue of an occupation certificate.

Please note: any Street or Sub-Address Numbering provided by an applicant on plans, which have been stamped as approved by Council are not to be interpreted as endorsed, approved by, or to the satisfaction of Council.

OPERATIONAL CONDITIONS

The following operational conditions must be complied with at all times, throughout the use and operation of the development.

These conditions have been applied to satisfy the relevant requirements of the *Environmental Planning & Assessment Act 1979*, *Environmental Planning & Assessment Regulation 2000*, Council's development consent and to maintain reasonable levels of public health and environmental amenity.

External Lighting

59. External lighting to the premises must be designed and located so as to minimise light-spill beyond the property boundary or cause a public nuisance.

Waste Management

60. Adequate provisions are to be made within the premises for the storage and removal of waste and recyclable materials, to the satisfaction of Council.

Plant & Equipment – Noise Levels

61. The operation of all plant and equipment on the premises shall not give rise to an 'offensive noise' as defined in the *Protection of the Environment Operations Act 1997 and Regulations*.

In this regard, the operation of the plant and equipment shall not give rise to an $L_{Aeq, 15 \text{ min}}$ sound pressure level at any affected premises that exceeds the background $L_{A90, 15 \text{ min}}$ noise level, measured in the absence of the noise source/s under consideration by more than 5dB(A) in accordance with relevant NSW Environment Protection Authority (EPA) Noise Control Guidelines.

Air Conditioners

62. Air conditioning plant and equipment shall not be operated during the following hours if the noise emitted can be heard within a habitable room in any other residential premises, or, as otherwise specified in relevant Noise Control Regulations:

- before 8.00am or after 10.00pm on any Saturday, Sunday or public holiday; or
- before 7.00am or after 10.00pm on any other day.

Rainwater Tanks

63. The operation of plant and equipment associated with rainwater tanks are to be restricted to the following hours if the noise emitted can be heard within a habitable room in any other residential premises:

- before 8.00am or after 8.00pm on weekends or public holiday; or
- before 7.00am or after 8.00pm on weekdays.

Use of parking spaces

64. The car spaces within the development are for the exclusive use of the occupants of the building. The car spaces must not be leased to any person/company that is not an occupant of the building.

ADVISORY NOTES

The following information is provided for your assistance to ensure compliance with the *Environmental Planning & Assessment Act 1979*, *Environmental Planning & Assessment Regulation 2000*, or other relevant legislation and Council's policies. This information does not form part of the conditions of development consent pursuant to Section 80A of the Act.

- A1 The requirements and provisions of the *Environmental Planning & Assessment Act 1979* and *Environmental Planning & Assessment Regulation 2000*, must be fully complied with at all times.

Failure to comply with these requirements is an offence, which renders the responsible person liable to a maximum penalty of \$1.1 million. Alternatively, Council may issue a penalty infringement notice (for up to \$3,000) for each offence. Council may also issue notices and orders to demolish unauthorised or non-complying building work, or to comply with the requirements of Council's development consent.

- A2 In accordance with the requirements of the *Environmental Planning & Assessment Act 1979*, building works, including associated demolition and excavation works (as applicable) must not be commenced until:

- A *Construction Certificate* has been obtained from an Accredited Certifier or Council,
- An Accredited Certifier or Council has been appointed as the *Principal Certifying Authority* for the development,
- Council and the Principal Certifying Authority have been given at least 2 days notice (in writing) prior to commencing any works.

- A3 Council can issue your *Construction Certificate* and be your *Principal Certifying Authority* for the development, to undertake inspections and ensure compliance with the development consent and relevant building regulations. For further details contact Council on 9093 6944.

- A4 This determination does not include an assessment of the proposed works under the Building Code of Australia (BCA) and other relevant Standards. All new building work (including alterations and additions) must comply with the BCA and relevant Standards and you are advised to liaise with your architect, engineer and building consultant prior to lodgement of your construction certificate.

- A5 A Local Approval application must be submitted to and be approved by Council's Building Approvals & Certification team prior to commencing any of the following activities on a footpath, road, nature strip or in any public place:-

- Install or erect any site fencing, hoardings or site structures
- Operate a crane or hoist goods or materials over a footpath or road
- Placement of a waste skip or any other container or article.

For further information please contact Council's Building Approvals & Certification team on 9093 6971.

- A6 Details of the location of the building/s should be provided in the Construction Certificate to demonstrate that the proposed building work will not encroach onto the adjoining properties, Council's road reserve or any public place.

- A7 This consent does not authorise any trespass or encroachment upon any adjoining or supported land or building whether private or public. Where any underpinning, shoring, soil anchoring (temporary or permanent) or the like is proposed to be carried out upon any adjoining or supported land, the land owner or principal contractor must obtain:

- the consent of the owners of such adjoining or supported land to trespass or encroach, or

- an access order under the *Access to Neighbouring Land Act 2000*, or
- an easement under section 88K of the *Conveyancing Act 1919*, or
- an easement under section 40 of the *Land & Environment Court Act 1979*, as appropriate.

Section 177 of the *Conveyancing Act 1919* creates a statutory duty of care in relation to support of land. Accordingly, a person has a duty of care not to do anything on or in relation to land being developed (the supporting land) that removes the support provided by the supporting land to any other adjoining land (the supported land).

- A8 The finished ground levels external to the building must be consistent with the development consent and are not to be raised, other than for the provision of approved paving or the like on the ground.
- A9 Prior to commencing any works, the owner/builder should contact *Dial Before You Dig* on 1100 or www.dialbeforeyoudig.com.au and relevant Service Authorities, for information on potential underground pipes and cables within the vicinity of the development site.
- A10 Underground assets (eg pipes, cables etc) may exist in the area that is subject to your application. In the interests of health and safety and in order to protect damage to third party assets please contact Dial before you dig at www.1100.com.au or telephone on 1100 before excavating or erecting structures (This is the law in NSW). If alterations are required to the configuration, size, form or design of the development upon contacting the Dial before You Dig service, an amendment to the development consent (or a new development application) may be necessary. Individuals owe asset owners a duty of care that must be observed when working in the vicinity of plant or assets. It is the individual's responsibility to anticipate and request the nominal location of plant or assets on the relevant property via contacting the Dial before you dig service in advance of any construction or planning activities.
- A11 The applicant is to advise Council in writing and/or photographs of any signs of existing damage to the Council roadway, footway, or verge prior to the commencement of any building/demolition works.
- A12 Further information and details on Council's requirements for trees on development sites can be obtained from the recently adopted Tree Technical Manual, which can be downloaded from Council's website at the following link, <http://www.randwick.nsw.gov.au> - Looking after our environment – Trees – Tree Management Technical Manual; which aims to achieve consistency of approach and compliance with appropriate standards and best practice guidelines.