

Development Consent Conditions



DA No:	DA/601/2018
Property:	59 Denning Street, SOUTH COOGEE NSW 2034
Proposal:	Alterations and additions to existing dual occupancy at lower ground, ground and first floor levels and conversion to a single dwelling, swimming pool to rear, garage to front, landscaping and associated works (variation to height control).
Recommendation:	Approval

Development Consent Conditions

GENERAL CONDITIONS

The development must be carried out in accordance with the following conditions of consent.

These conditions have been applied to satisfy the relevant requirements of the *Environmental Planning & Assessment Act 1979*, *Environmental Planning & Assessment Regulation 2000* and to provide reasonable levels of environmental amenity.

Approved Plans & Supporting Documentation

- The development must be implemented substantially in accordance with the plans and supporting documentation listed below and endorsed with Council's approved stamp, except where amended by Council in red and/or by other conditions of this consent:

Plan	Drawn by	Dated
Proposed Site & Roof Plan - Drawing Number 02	Living Lot	27/02/2019
LGF Demo - Drawing Number 03	Living Lot	27/02/2019
Lower Ground Floor - Proposed Drawing Number 04	Living Lot	27/02/2019
GF Demo - Drawing Number 05	Living Lot	27/02/2019
Ground Floor - Proposed Drawing Number 06	Living Lot	27/02/2019
L1 Demo - Drawing Number 07	Living Lot	27/02/2019
Level 1 - Proposed - Drawing Number 08	Living Lot	27/02/2019
West & East Elevations - Proposed Drawing Number 09	Living Lot	27/02/2019
South Elevation - Proposed Drawing Number 10	Living Lot	27/02/2019
North Elevation - Proposed Drawing Number 11	Living Lot	27/02/2019
Long Section 1-1 - Drawing Number 12	Living Lot	27/02/2019
Short Sections 2-2 & 3-3 - Drawing Number 13	Living Lot	27/02/2019
Pool Section 4-4 - Drawing Number 14	Living Lot	27/02/2019
North Boundary Fence Section A-A- Drawing Number 15	Living Lot	27/02/2019
South Boundary Fence Section B-B - Drawing Number 16	Living Lot	27/02/2019
Window & Door Plan -Drawing Number 18	Living Lot	27/02/2019
Basix, Window & Door Schedule - Drawing Number 19	Living Lot	27/02/2019
Landscaping Layout	Green Mouse	26/02/2019
Sections	Green Mouse	26/02/2019

BASIX Certificate No.	Dated
------------------------------	--------------

Amendment of Plans & Documentation

2. The approved plans and documents must be amended in accordance with the following requirements:

- a. A privacy screen having a height of 1.8m measured above the finished floor level shall be provided to the northern side elevation of the balcony at the rear of the L1 plan.

The privacy screen must be constructed with either:

- Translucent or obscured glazing (The use of film applied to the clear glass pane is unacceptable);
- Fixed lattice/slats with individual openings not more than 30mm wide;
- Fixed vertical or horizontal louvres with the individual blades angled and spaced appropriately to prevent overlooking into the private open space or windows of the adjacent dwellings.

- b. The width of the balcony at the rear of the L1 plan shall be reduced from 3.98m to 2.26m to align with the external face of the floor below.

REQUIREMENTS BEFORE A CONSTRUCTION CERTIFICATE CAN BE ISSUED

The following conditions of consent must be complied with before a 'Construction Certificate' is issued by either Randwick City Council or an Accredited Certifier. All necessary information to demonstrate compliance with the following conditions of consent must be included in the documentation for the construction certificate.

These conditions have been applied to satisfy the relevant requirements of the *Environmental Planning & Assessment Act 1979*, *Environmental Planning & Assessment Regulation 2000*, Council's development consent conditions and to achieve reasonable levels of environmental amenity.

Consent Requirements

3. The requirements and amendments detailed in the 'General Conditions' must be complied with and be included in the construction certificate plans and associated documentation.

External Colours, Materials & Finishes

4. a) The colours, materials and finishes of the external surfaces are to be compatible with the existing building and adjacent development to maintain the integrity and amenity of the building and the streetscape.

External materials, finishes and colours of the building are required to match, as closely as possible, the existing building and any metal roof sheeting is to be pre-painted (e.g. Colourbond) to limit the level of reflection and glare.

Section 7.12 Development Contributions

5. In accordance with Council's Development Contributions Plan effective from 21 April 2015, based on the development cost of \$680,186 the following applicable monetary levy must be paid to Council: \$6,801.86.

The levy must be paid in **cash, bank cheque** or by **credit card** prior to a construction certificate being issued for the proposed development. The development is subject to an index to reflect quarterly variations in the Consumer Price Index (CPI) from the date of Council's determination to the date of payment.

Please contact Council on telephone 9093 6999 or 1300 722 542 for the indexed contribution amount prior to payment.

To calculate the indexed levy, the following formula must be used:

$$\text{IDC} = \text{ODC} \times \text{CP2/CP1}$$

Where:

IDC = the indexed development cost

ODC = the original development cost determined by the Council

CP2 = the Consumer Price Index, All Groups, Sydney, as published by the ABS in respect of the quarter ending immediately prior to the date of payment

CP1 = the Consumer Price Index, All Groups, Sydney as published by the ABS in respect of the quarter ending immediately prior to the date of imposition of the condition requiring payment of the levy.

Council's Development Contributions Plans may be inspected at the Customer Service Centre, Administrative Centre, 30 Frances Street, Randwick or at www.randwick.nsw.gov.au.

Compliance Fee

6. A development compliance and enforcement fee of \$680 shall be paid to Council in accordance with Council's adopted Fees & Charges Pricing Policy, prior to the issue of a Construction Certificate for development.

Long Service Levy Payments

7. The required Long Service Levy payment, under the *Building and Construction Industry Long Service Payments Act 1986*, must be forwarded to the Long Service Levy Corporation or the Council, in accordance with Section 6.8 of the *Environmental Planning & Assessment Act 1979*.

At the time of this development consent, Long Service Levy payment is applicable on building work having a value of \$25,000 or more, at the rate of 0.35% of the cost of the works.

Security Deposits

8. The following security deposits requirement must be complied with prior to a construction certificate being issued for the development, as security for making good any damage caused to Council's assets and infrastructure; and as security for completing any public work; and for remedying any defect on such public works, in accordance with section 4.17(6) of the *Environmental Planning and Assessment Act 1979*:

- \$4000.00 - Damage / Civil Works Security Deposit

Security deposits may be provided by way of a cash, cheque or credit card payment and is refundable upon a satisfactory inspection by Council upon the completion of the civil works which confirms that there has been no damage to Council's infrastructure.

The owner/builder is also requested to advise Council in writing and/or photographs of any signs of existing damage to the Council roadway, footway, or verge prior to the commencement of any building/demolition works.

To obtain a refund of relevant deposits, a *Security Deposit Refund Form* is to be forwarded to Council's Director of City Services upon issuing of an occupation certificate or completion of the civil works.

Design Alignment Levels

9. The design alignment level (the finished level of concrete, paving or the like) at the property boundary for driveways, access ramps and pathways or the like, shall be:

Vehicle crossing - Northern edge

- **RL 45.99 AHD being approximately 20mm above the back of the existing Council footpath level opposite.**

Vehicle crossing - Southern edge

- **RL 46.15 AHD being approximately 20mm above the back of the existing Council footpath level opposite.**

Pedestrian Entrance

- **RL 45.90 AHD being approximately 20mm above the back of the existing Council footpath level opposite.**

The design alignment levels at the property boundary as issued by Council and their relationship to the footpath must be indicated on the building plans for the construction certificate (a construction note on the plans is considered satisfactory). The design alignment level at the street boundary, as issued by the Council, must be strictly adhered to.

Any request to vary the design alignment level/s must be forwarded to and approved in writing by Council's Development Engineers and may require a formal amendment to the development consent via a Section 4.55 application.

Enquiries regarding this matter should be directed to Council's Development Engineer on 9093-6881.

10. The above alignment levels and the site inspection by Council's Development Engineer have been issued at a prescribed fee of **\$159**. This amount is to be paid prior to a construction certificate being issued for the development.

Driveway & Garage Design

11. Plans submitted for the construction certificate shall demonstrate compliance with the following requirements and amendments;
- a) The gradient of the internal access driveway must be designed and constructed to not exceed a grade of 1 in 8 (12.5%).
 - b) The Garage Floor level shall be raised to RL 46.10 AHD or a crossfall introduced to ensure the maximum grades are not exceeded along southern edge.
 - c) The levels of the driveway must match the alignment levels at the property boundary (as specified by Council).

Stormwater Drainage

12. To achieve compliance with Council's current Private Stormwater Code and Australia standard 3500.2, an upgrade of the site's stormwater system will be required. Detailed drainage plans with levels reduced to Australian Height Datum (AHD), shall be prepared by a suitably qualified Hydraulic Engineer and be submitted to and approved by the certifying authority. A copy of the plans shall be forwarded to Council, if Council is not the certifying authority.

The drainage plans must demonstrate compliance with the Building Code of Australia, Australian Standard AS3500.3:2003 (Plumbing and Drainage - Stormwater Drainage) and the relevant conditions of this development approval.

13. Stormwater runoff from the (redeveloped portion) site shall be discharged either:
- a. To the kerb and gutter along the site frontage by gravity (preferably without the use of a charged system); OR
 - b. Through a private drainage easement(s) to Council's kerb and gutter (or underground drainage system); OR
 - c. To a suitably sized infiltration area. As a guide the infiltration area shall be sized based on a minimum requirement of 1 m² of infiltration area (together with 1 m³ of storage volume) for every 20 m² of roof/impervious area on the site.

Infiltration areas must be located a minimum of 3.0 metres from any structure (note: this set back requirement may not be necessary if a structural engineer or other suitably qualified person certifies that the infiltration area will not adversely affect the structure) and 2.1 metres from any adjacent side or rear boundary.

Prior to the use of infiltration in rear draining lots (where there is no formal overland escape route to Council's kerb and gutter/street drainage system), a geotechnical investigation will be required to determine whether the ground is suitable for infiltration. Should rock and/or a water table be encountered within two metres of the proposed base of the infiltration pit, or the ground conditions comprise low permeability soils such as clay, infiltration will not be appropriate.

NOTE: Should the applicant be unable to obtain a private drainage easement over properties to the rear of the development site (to facilitate stormwater discharge in accordance with option b)); and ground conditions preclude the use of infiltration (Option c), consideration may be given to the use of a charged system or a pump out system to drain that portion of the site that cannot be drained by gravity to the kerb and gutter at the front of the property.

14. Should a charged system be required to drain any portion of the site, the charged system must be designed such that;
- i. There are suitable clear-outs/inspection points at pipe bends and junctions.
 - ii. The maximum depth of the charged line does not exceed 1m below the gutter outlet.
15. Should a pump system be required to drain any portion of the site the system must be designed with a minimum of two pumps being installed, connected in parallel (with each pump capable of discharging at the required discharge rate) and connected to a control board so that each pump will operate alternatively. The pump wet well shall be sized for the 1 in 100 year, 2 hour storm assuming both pumps are not working.

The pump system must also be designed and installed strictly in accordance with Randwick City Council's Stormwater Code.

16. All pump out water must pass through a stilling pit, located within the site, prior to being discharged by gravity to the kerb and gutter.

Sydney Water

17. All building, plumbing and drainage work must be carried out in accordance with the requirements of the Sydney Water Corporation.

The approved plans must be submitted to the Sydney Water **Tap in™** online service, to determine whether the development will affect Sydney Water's waste water and water mains, stormwater drains and/or easements, and if any further requirements need to be met.

The **Tap in™** service provides 24/7 access to a range of services, including:

- Building plan approvals
- Connection and disconnection approvals
- Diagrams
- Trade waste approvals
- Pressure information
- Water meter installations
- Pressure boosting and pump approvals
- Change to an existing service or asset, e.g. relocating or moving an asset.

Sydney Water's **Tap in™** in online service is available at:
<https://www.sydneywater.com.au/tapin>

The Principal Certifying Authority must ensure that the developer/owner has submitted the approved plans to Sydney Water Tap in online service.

Street Tree Management

18. The applicant must submit a payment of **\$357.25** (plus GST) to cover the following costs:
- a. For Council to remove, stump-grind and dispose of the existing *Grevillea* from the Denning Street verge, centrally across the width of the site, so as to accommodate the new vehicle crossing and garage in this same location as shown;
 - b. For Council to supply, plant and maintain 1 x 25 litre replacement *Grevillea* of the same species back on the verge, around the northern site boundary, at the completion of all works.

This fee must be paid into **Tree Amenity Income** at the Cashier on the Ground Floor of the Administrative Centre **prior to a Construction Certificate being issued for the development.**

The applicant must contact Council's Landscape Development Officer on 9093-6613 (quoting the receipt number), and giving at least four working weeks-notice (allow longer for public holidays or extended periods of rain) to arrange for removal of the street tree prior to the commencement of site works, as well as upon completion, to arrange for planting of the replacement street tree.

After this, any further enquiries regarding scheduling/timing or completion of tree works are to be directed to Council's North Area Tree Preservation & Maintenance Coordinator on 9093-6858.

REQUIREMENTS TO BE INCLUDED IN THE CONSTRUCTION CERTIFICATE

The requirements contained in the following conditions of consent must be complied with and details of compliance must be included in the construction certificate for the development.

These conditions have been applied to satisfy the relevant requirements of the *Environmental Planning & Assessment Act 1979*, *Environmental Planning & Assessment Regulation 2000*, Councils development consent conditions and to achieve reasonable levels of environmental amenity.

Compliance with the Building Code of Australia

19. In accordance with section 4.17 (11) of the *Environmental Planning & Assessment Act 1979* and clause 98 of the *Environmental Planning & Assessment Regulation 2000*, it is a *prescribed condition* that all building work must be carried out in accordance with the provisions of the Building Code of Australia (BCA). Details of compliance with the BCA are to be included in the construction certificate application.

Structural Adequacy

20. Certificate of Adequacy supplied by a *professional engineer* shall be submitted to the *certifying authority (and the Council, if the Council is not the certifying authority)*, certifying the structural adequacy of the existing structure to support the proposed additions.

Driveway Design

21. The gradient of the internal access driveway must be designed and constructed in accordance with AS 2890.1 (2004) – Off Street Car Parking and the levels of the driveway must match the alignment levels at the property boundary (as specified by Council). Details of compliance are to be included in the construction certificate.

BASIX Requirements

22. In accordance with section 4.17(11) of the *Environmental Planning & Assessment Act 1979* and clause 97A of the *Environmental Planning & Assessment Regulation 2000*, the requirements and commitments contained in the relevant BASIX Certificate must be complied with.

The required commitments listed and identified in the BASIX Certificate must be included on the construction certificate plans, specifications and associated documentation, to the satisfaction of the Certifying Authority.

The design of the building must not be inconsistent with the development consent and any proposed variations to the building to achieve the BASIX commitments may necessitate a new development consent or amendment to the existing consent to be obtained, prior to a construction certificate being issued.

REQUIREMENTS PRIOR TO THE COMMENCEMENT OF ANY WORKS

The following conditions of consent must be complied with prior to the commencement of any works on the site. The necessary documentation and information must be provided to the Council or the '*Principal Certifying Authority*' (PCA), as applicable.

These conditions have been applied to satisfy the relevant requirements of the *Environmental Planning & Assessment Act 1979*, *Environmental Planning & Assessment Regulation 2000* and to provide reasonable levels of public health, safety and environmental amenity.

Certification, PCA & Other Requirements

23. Prior to the commencement of any building works, the following requirements must be complied with:

- a) a *Construction Certificate* must be obtained from the Council or an accredited certifier, in accordance with the provisions of the *Environmental Planning & Assessment Act 1979*.

A copy of the construction certificate, the approved development consent plans and consent conditions must be kept on the site at all times and be made available to the Council officers and all building contractors for assessment.

- b) a *Principal Certifying Authority* (PCA) must be appointed to carry out the necessary building inspections and to issue an *occupation certificate*; and
- c) a *principal contractor* must be appointed for the building work, or in relation to residential building work, an *owner-builder* permit may be obtained in accordance with the requirements of the *Home Building Act 1989*, and the PCA and Council are to be notified accordingly; and
- d) the *principal contractor* must be advised of the required *critical stage inspections* and other inspections to be carried out, as specified by the *Principal Certifying Authority*; and
- e) at least two days notice must be given to the Council, in writing, prior to commencing any works.

Home Building Act 1989

24. In accordance with section 4.17 (11) of the *Environmental Planning & Assessment Act 1979* and clause 98 of the *Environmental Planning & Assessment Regulation 2000*, the requirements of the *Home Building Act 1989* must be complied with.

Details of the Licensed Building Contractor and a copy of the relevant Certificate of Home Warranty Insurance or a copy of the Owner-Builder Permit (as applicable) must be provided to the Principal Certifying Authority and Council.

Dilapidation Reports

25. A dilapidation report must be obtained from a Professional Engineer, Building Surveyor or other suitably qualified independent person, in the following cases:

- excavations for new dwellings, additions to dwellings, swimming pools or other substantial structures which are proposed to be located within the *zone of influence* of the footings of any dwelling, associated garage or other substantial structure located upon an adjoining premises;
- new dwellings or additions to dwellings sited up to shared property boundaries (e.g. additions to a semi-detached dwelling or terraced dwellings);
- excavations for new dwellings, additions to dwellings, swimming pools or other substantial structures which are within rock and may result in vibration and or potential damage to any dwelling, associated garage or other substantial structure located upon an adjoining premises;
- as otherwise may be required by the *Principal Certifying Authority*.

The dilapidation report shall include details of the current condition and status of any dwelling, associated garage or other substantial structure located upon the adjoining premises and shall include relevant photographs of the structures, to the satisfaction of the *Principal Certifying Authority*.

The dilapidation report must be submitted to the Council, the *Principal Certifying Authority* and the owners of the adjoining/nearby premises encompassed in the report, prior to commencing any site works (including any demolition work, excavation work or building work).

Construction Noise & Vibration Management Plan

26. Noise and vibration emissions during the construction of the building and associated site works must not result in an unreasonable loss of amenity to nearby residents and the relevant requirements of the *Protection of the Environment Operations Act 1997* and NSW EPA Guidelines must be satisfied at all times.

Noise and vibration from any rock excavation machinery, pile drivers and all plant and equipment must be minimised, by using appropriate plant and equipment, silencers and the implementation of noise management strategies.

A *Construction Noise Management Plan*, prepared in accordance with the NSW EPA Construction Noise Guideline by a suitably qualified person, is to be implemented throughout the works. A copy of the strategy must be provided to the Principal Certifying Authority and Council prior to the commencement of works on site.

Construction Site Management Plan

27. A *Construction Site Management Plan* must be developed and implemented prior to the commencement of any works. The construction site management plan must include the following measures, as applicable to the type of development:

- location and construction of protective fencing / hoardings to the perimeter of the site;
- location of site storage areas/sheds/equipment;
- location of building materials for construction;
- provisions for public safety;
- dust control measures;
- site access location and construction;
- details of methods of disposal of demolition materials;
- protective measures for tree preservation;
- provisions for temporary sanitary facilities;
- location and size of waste containers/bulk bins;
- details of proposed sediment and erosion control measures;
- provisions for temporary stormwater drainage;
- construction noise and vibration management;
- construction traffic management details.

The site management measures must be implemented prior to the commencement of any site works and be maintained throughout the works.

A copy of the *Construction Site Management Plan* must be provided to the *Principal Certifying Authority* and Council prior to commencing site works. A copy must also be maintained on site and be made available to Council officers upon request.

Demolition Work Plan

28. Demolition Work must be carried out in accordance with Australian Standard AS2601-2001, Demolition of Structures and relevant work health and safety provisions and the following requirements:

- a) A Demolition Work Plan must be prepared for the demolition works which should be submitted to the Principal Certifying Authority (PCA), not less than two (2) working days before commencing any demolition work. A copy of

the Demolition Work Plan must be maintained on site and be made available to Council officers upon request.

If the work involves asbestos products or materials, a copy of the Demolition Work Plan must also be provided to Council not less than 2 days before commencing those works.

- a) Any materials containing asbestos (including Fibro) must be safely removed and disposed of in accordance with the NSW Work Health and Safety Regulation 2017, SafeWork NSW Code of Practice for the Safe Removal of Asbestos, Protection of Environment Operations (Waste) Regulation 2014 and Council's Asbestos Policy.

Public Utilities

29. A *Public Utility Impact Assessment* must be carried out on all public utility services on the site, roadway, nature strip, footpath, public reserve or any public areas associated with and/or adjacent to the development/building works and include relevant information from public utility authorities and exploratory trenching or pot-holing, if necessary, to determine the position and level of service.
30. The applicant must meet the full cost for telecommunication companies, gas providers, Ausgrid, and Sydney Water to adjust/repair/relocate their services as required. The applicant must make the necessary arrangements with the service authority.

Landscape Plan

31. For a development of this type, a landscape plan that has been prepared by a qualified professional in the Landscape/Horticultural industry (must be eligible for membership with AILD, AILA or equivalent) must be submitted to, and be approved by, the Certifying Authority/PCA, **prior to the commencement of site works**, and must detail the following:
 - a) A Planting Plan & Plant Schedule which includes proposed species, botanic and common names, pot size at the time of planting, quantity, location, dimensions at maturity and any other details required to describe the works. All new plantings around the perimeter of the swimming pool shall not exceed 3m mature height;
 - b) A predominance of species that can withstand poor quality sandy soils, salt laden winds and are not reliant on high quantities of moisture and fertilizer for survival;
 - c) A high quality selection and arrangement of decorative species throughout the front setback so as to assist with presentation of the development to the streetscape;
 - d) Dedicated garden areas around the perimeter of the rear setback, to which, strategically selected and located screen planting as well as decorative lower growing species shall be provided in order provide reasonable levels of environmental amenity between this site and neighbouring sites, as well as to cater to the amenity needs of future occupants.

REQUIREMENTS DURING CONSTRUCTION & SITE WORK

The following conditions of consent must be complied with during the demolition, excavation and construction of the development.

These conditions have been applied to satisfy the relevant requirements of the *Environmental Planning & Assessment Act 1979*, *Environmental Planning & Assessment Regulation 2000* and to provide reasonable levels of public health, safety and environmental amenity during construction.

Inspections during Construction

32. Building works are required to be inspected by the *Principal Certifying Authority*, in accordance with the *Environmental Planning & Assessment Act 1979* and clause 162A of the *Environmental Planning & Assessment Regulation 2000*, to monitor compliance with the relevant standards of construction, Council’s development consent and the construction certificate.

Site Signage

33. A sign must be erected and maintained in a prominent position on the site for the duration of the works, which contains the following details:
- name, address, contractor licence number and telephone number of the *principal contractor*, including a telephone number at which the person may be contacted outside working hours, or *owner-builder* permit details (as applicable)
 - name, address and telephone number of the *Principal Certifying Authority*,
 - a statement stating that “unauthorised entry to the work site is prohibited”.

Restriction on Working Hours

34. Building, demolition and associated site works must be carried out in accordance with the following requirements:

Activity	Permitted working hours
All building, demolition and site work, including site deliveries (except as detailed below)	<ul style="list-style-type: none"> • Monday to Friday - 7.00am to 5.00pm • Saturday - 8.00am to 5.00pm • Sunday & public holidays - No work permitted
Excavating or sawing of rock, use of jack-hammers, pile-drivers, vibratory rollers/compactors or the like	<ul style="list-style-type: none"> • Monday to Friday - 8.00am to 1.00pm • Saturday - No work permitted • Sunday & public holidays - No work permitted

An application to vary the abovementioned hours may be submitted to Council’s Manager Health, Building & Regulatory Services for consideration and approval to vary the specified hours may be granted in exceptional circumstances and for limited occasions (e.g. for public safety, traffic management or road safety reasons). Any applications are to be made on the standard application form and include payment of the relevant fees and supporting information. Applications must be made at least 10 days prior to the date of the proposed work and the prior written approval of Council must be obtained to vary the standard permitted working hours.

Removal of Asbestos Materials

35. Any work involving the demolition, storage or disposal of asbestos products and materials must be carried out in accordance with the following requirements:
- Work Health & Safety legislation and SafeWork NSW requirements
 - Preparation and implementation of a *demolition work plan*, in accordance with AS 2601 (2001) – Demolition of structures; NSW Work Health and Safety Regulation 2017 and Randwick City Council’s Asbestos Policy. A copy of the demolition work plan must be provided to Principal Certifying

Authority and a copy must be kept on site and be made available for Council Officer upon request.

- A SafeWork NSW licensed demolition or asbestos removal contractor must undertake removal of more than 10m² of bonded asbestos (or as otherwise specified by SafeWork NSW or relevant legislation). Removal of friable asbestos material must only be undertaken by contractor that holds a current friable asbestos removal licence. A copy of the relevant licence must be provided to the Principal Certifying Authority.
- On sites involving the removal of asbestos, a sign must be clearly displayed in a prominent visible position at the front of the site, containing the words 'Danger Asbestos Removal In Progress' and include details of the licensed contractor.
- Asbestos waste must be stored, transported and disposed of in compliance with the *Protection of the Environment Operations Act 1997* and the *Protection of the Environment Operations (Waste) Regulation 2014*. Details of the disposal of materials containing asbestos (including receipts) must be provided to the Principal Certifying Authority and Council.
- A Clearance Certificate or Statement, prepared by a suitably qualified person (i.e. an occupational hygienist, licensed asbestos assessor or other competent person), must be provided to Council and the Principal Certifying Authority as soon as practicable after completion of the asbestos related works, which confirms that the asbestos material have been removed appropriately and the relevant conditions of consent have been satisfied.

A copy of Council's Asbestos Policy is available on Council's web site at www.randwick.nsw.gov.au in the Building & Development Section or a copy can be obtained from Council's Customer Service Centre.

Public Safety & Site Management

36. Public safety and convenience must be maintained at all times during demolition, excavation and construction works and the following requirements must be complied with:

- a) Public access to the building site and materials must be restricted by existing boundary fencing or temporary site fencing having a minimum height of 1.5m, to Council's satisfaction.

Temporary site fences are required to be constructed of cyclone wire fencing material and be structurally adequate, safe and constructed in a professional manner. The use of poor quality materials or steel reinforcement mesh as fencing is not permissible.

- b) Building materials, sand, soil, waste materials, construction equipment or other articles must not be placed upon the footpath, roadway or nature strip at any time.
- c) The road, footpath, vehicular crossing and nature strip must be maintained in a good, safe, clean condition and free from any excavations, obstructions, trip hazards, goods, materials, soils or debris at all times. Any damage caused to the road, footway, vehicular crossing, nature strip or any public place must be repaired immediately, to the satisfaction of Council.
- d) All building and site activities (including storage or placement of materials or waste and concrete mixing/pouring/pumping activities) must not cause or

be likely to cause 'pollution' of any waters, including any stormwater drainage systems, street gutters or roadways.

Note: It is an offence under the Protection of the Environment Operations Act 1997 to cause or be likely to cause 'pollution of waters', which may result in significant penalties and fines.

- e) Sediment and erosion control measures, must be implemented throughout the site works in accordance with the manual for Managing Urban Stormwater – Soils and Construction, published by Landcom, and details are to be included in the *Construction site Management Plan*.
- a) Site fencing, building materials, bulk bins/waste containers and other articles must not be located upon the footpath, roadway or nature strip at any time without the prior written approval of the Council. Applications to place a waste container in a public place can be made to Council's Health, Building and Regulatory Services department.
- b) Adequate provisions must be made to ensure pedestrian safety and traffic flow during the site works and traffic control measures are to be implemented in accordance with the relevant provisions of the Roads and Traffic Manual "Traffic Control at Work Sites" (Version 4), to the satisfaction of Council.

Support of Adjoining Land, Excavations & Retaining Walls

- 37. In accordance with section 4.17 (11) of the *Environmental Planning & Assessment Act 1979* and clause 98 E of the *Environmental Planning & Assessment Regulation 2000*, it is a prescribed condition that the adjoining land and buildings located upon the adjoining land must be adequately supported at all times.
- 38. All excavations and backfilling associated with the erection or demolition of a building must be executed safely in accordance with appropriate professional standards and excavations must be properly guarded and supported to prevent them from being dangerous to life, property or buildings.

Retaining walls, shoring or piling must be provided to support land which is excavated in association with the erection or demolition of a building, to prevent the movement of soil and to support the adjacent land and buildings, if the soil conditions require it. Adequate provisions are also to be made for drainage.

Details of proposed retaining walls, shoring, piling or other measures are to be submitted to and approved by the Principal Certifying Authority.

- 39. Prior to undertaking any demolition, excavation or building work in the following circumstances, a report must be obtained from a *professional engineer* which details the methods of support for the dwelling or associated structure on the adjoining land, to the satisfaction of the *Principal Certifying Authority*:
 - when undertaking excavation or building work within the zone of influence of the footings of a dwelling or associated structure that is located on the adjoining land;
 - when undertaking demolition work to a wall of a dwelling that is built to a common or shared boundary (e.g. semi-detached or terrace dwelling);
 - when constructing a wall to a dwelling or associated structure that is located within 900mm of a dwelling located on the adjoining land;
 - as may be required by the *Principal Certifying Authority*.

The demolition, excavation and building work and the provision of support to the dwelling or *associated* structure on the adjoining land, must also be carried out in accordance with the abovementioned report, to the satisfaction of the *Principal Certifying Authority*.

Building Encroachments

40. There must be no encroachment of any structures or building work onto Council's road reserve, footway, nature strip or public place.

Tree Management

41. Approval is granted for removal of the following vegetation from within the subject site, subject to full implementation of the approved Landscape Plan:
- a) The Oleander in the front setback, in the northwest site corner, as it is an undesirable, exempt species in Council's DCP, that could already be removed at anytime, without consent, with the new works also shown for this same area, along with the two small Grevillea's immediately to its south for the same reason;
 - b) The two rows of vegetation in the rear yard, being two specimens along the southern boundary, around the southeast corner, and three along the northern boundary, around the northeast site corner, as none are significant in anyway.

Road/Asset Opening Permit

42. A *Road / Asset Opening Permit* must be obtained from Council prior to commencing any excavations or works within or upon a road, footpath, nature strip or in any public place, in accordance with section 138 of the *Roads Act 1993* and all of the conditions and requirements contained in the *Road / Asset Opening Permit* must be complied with.

For further information, please contact Council's Road / Asset Opening Officer on 9093 6691 or 1300 722 542.

REQUIREMENTS PRIOR TO THE ISSUE OF AN OCCUPATION CERTIFICATE

The following conditions of consent must be complied with prior to the '*Principal Certifying Authority*' issuing an '*Occupation Certificate*'.

Note: For the purpose of this consent, any reference to 'occupation certificate' shall also be taken to mean 'interim occupation certificate' unless otherwise stated.

These conditions have been applied to satisfy the relevant requirements of the *Environmental Planning & Assessment Act 1979*, *Environmental Planning & Assessment Regulation 2000*, Council's development consent and to maintain reasonable levels of public health, safety and amenity.

Occupation Certificate Requirements

43. An Occupation Certificate must be obtained from the *Principal Certifying Authority* prior to any occupation of the building work encompassed in this development consent (including alterations and additions to existing buildings), in accordance with the relevant provisions of the *Environmental Planning & Assessment Act 1979*.

BASIX Requirements

44. In accordance with Clause 154B of the *Environmental Planning & Assessment Regulation 2000*, a *Certifying Authority* must not issue an Occupation Certificate

for this development, unless it is satisfied that each of the required BASIX commitments have been fulfilled.

Relevant documentary evidence of compliance with the BASIX commitments is to be forwarded to the Council upon issuing an Occupation Certificate.

Swimming Pool Safety

45. Swimming pools are to be designed and installed in accordance with the relevant requirements of the *Building Code of Australia* and be provided with childproof fences and self-locking gates, in accordance with the *Swimming Pools Act 1992* and the *Swimming Pools Regulation 2008*.

The swimming pool is to be surrounded by a child-resistant barrier (e.g. fence), that separates the pool from any *residential building* (as defined in the *Swimming Pools Act 1992*) that is situated on the premises and from any place (whether public or private) adjoining the premises; and that is designed, constructed and installed in accordance with Australian Standard AS 1926.1 – 2012 (Swimming Pool Safety Part 1 - Safety Barriers for Swimming Pools).

Gates to pool area must be self-closing and latching at all times and, the gate is required to open outwards from the pool area and prevent a small child opening the gate or door when the gate or door is closed.

Temporary pool safety fencing is to be provided pending the completion of all building work and the pool must not be filled until a fencing inspection has been carried out and approved by the principal certifying authority.

A 'warning notice' must be erected in a prominent position in the immediate vicinity of the swimming pool, in accordance with the provisions of the *Swimming Pools Regulation 2008*, detailing pool safety requirements, resuscitation techniques and the importance of the supervision of children at all times.

Swimming Pool & Spa Pool Requirements

46. Swimming pools (and spa pools) are to be designed, installed and operated in accordance with the following general requirements:

- a) Backwash of the pool filter and other discharge of water is to be drained to the sewer in accordance with the requirements of the Sydney Water Corporation; and
- a) All pool overflow water is to be drained away from the building and adjoining premises, so as not to result in a nuisance or damage to premises; and
- b) Water recirculation and filtrations systems are required to comply with AS 1926.3 – 2010: *Swimming Pool Safety – Water Recirculation and Filtration Systems*; and
- c) Pool plant and equipment is to be enclosed in a sound absorbing enclosure or installed within a building, to minimise noise emissions and possible nuisance to nearby residents.

Notification of Swimming Pools & Spa Pools

47. The owner of the premises must 'register' the swimming pool [or spa pool] on the NSW Swimming Pool Register, in accordance with the *Swimming Pools Amendment Act 2012*.

The Swimming Pool Register is administered by the NSW Office of Local Government and registration on the Swimming Pool Register may be made on-line via their website www.swimmingpoolregister.nsw.gov.au.

Registration must be made before the issue of an Occupation Certificate for the pool.

Council's Infrastructure, Vehicular Crossings, street verge

48. The applicant must meet the full cost for a Council approved contractor to:
 - a. Construct a concrete vehicular crossing and layback at kerb opposite the vehicular entrance to the site to Council's specifications and requirements.
49. The applicant must meet the full cost for Council or a Council approved contractor to repair/replace any damaged sections of Council's footpath, kerb & gutter, nature strip etc which are due to building works being carried out at the above site. This includes the removal of cement slurry from Council's footpath and roadway.
50. All external civil work to be carried out on Council property (including the installation and repair of roads, footpaths, vehicular crossings, kerb and guttering and drainage works), must be carried out in accordance with Council's "Crossings and Entrances – Contributions Policy" and "Residents' Requests for Special Verge Crossings Policy" and the following requirements:
 - a) Details of the proposed civil works to be carried out on Council land must be submitted to Council in a Civil Works Application Form. Council will respond, typically within 4 weeks, with a letter of approval outlining conditions for working on Council land, associated fees and workmanship bonds. Council will also provide details of the approved works including specifications and construction details.
 - b) Works on Council land, must not commence until the written letter of approval has been obtained from Council and heavy construction works within the property are complete. The work must be carried out in accordance with the conditions of development consent, Council's conditions for working on Council land, design details and payment of the fees and bonds outlined in the letter of approval.
 - c) The civil works must be completed in accordance with the above, prior to the issuing of an occupation certificate for the development, or as otherwise approved by Council in writing.

Stormwater Drainage

51. The applicant shall submit to the Principal Certifying Authority (PCA) and Council, certification from a suitably qualified and experienced Hydraulic Engineer confirming that the design and construction of the stormwater drainage system complies with Australian Standard 3500.3:2003 (Plumbing & Drainage-Stormwater Drainage) and the conditions of this development approval. The certification must be provided following inspection/s of the site stormwater drainage system by the certifying engineers and shall be provided to the satisfaction of the PCA.
52. Should a infiltration area or pump-out system be provided, a works-as-executed drainage plan prepared by a registered surveyor and approved by a suitably qualified and experienced hydraulic consultant/engineer must be forwarded to the Principal Certifying Authority and the Council. The works-as-executed plan must include the following details (as applicable):

- The location, diameter, gradient and material (i.e. PVC, RC etc) of all stormwater pipes;
- Details of infiltration/absorption systems; and
- Details of pumping systems installed (including wet well volumes).

53. Should a infiltration area or pump-out system be provided, a "restriction on the use of land" and "positive covenant" (under section 88E of the Conveyancing Act 1919) shall be placed on the title of the subject property to ensure that the onsite infiltration/pump-out system is maintained and that no works which could affect the design function of the infiltration/pump-out system are undertaken without the prior consent (in writing) from Council. Such restriction and positive covenant shall not be released, varied or modified without the consent of the Council.

Notes:

- a. The "restriction on the use of land" and "positive covenant" are to be to the satisfaction of Council. A copy of Council's standard wording/layout for the restriction and positive covenant may be obtained from Council's Development Engineer.
- b. The works as executed drainage plan and hydraulic certification must be submitted to Council prior to the "restriction on the use of land" and "positive covenant" being executed by Council.

Landscaping

54. The PCA must ensure that landscaping at this site has been installed in accordance with the approved plan and relevant conditions of consent, prior to the issue of any Occupation Certificate, with the owner/s to maintain it in a healthy and vigorous state until maturity.
55. The nature-strip upon Council's footway shall be re-graded and re-turfed with Kikuyu Turf rolls, including turf underlay, wholly at the applicant's cost, to Council's satisfaction, prior to the issue of any Occupation Certificate.

Street and/or Sub-Address Numbering

56. Street numbering must be provided to the front of the premises in a prominent position, in accordance with the Australia Post guidelines and AS/NZS 4819 (2003) to the satisfaction of Council.

If this application results in an additional lot, dwelling or unit, an application must be submitted to and approved by Council's Director of City Planning, together with the required fee, for the allocation of appropriate street and/or unit numbers for the development. The street and/or unit numbers must be allocated prior to the issue of an occupation certificate.

Please note: any Street or Sub-Address Numbering provided by an applicant on plans, which have been stamped as approved by Council are not to be interpreted as endorsed, approved by, or to the satisfaction of Council.

OPERATIONAL CONDITIONS

The following operational conditions must be complied with at all times, throughout the use and operation of the development.

These conditions have been applied to satisfy the relevant requirements of the *Environmental Planning & Assessment Act 1979, Environmental Planning & Assessment Regulation 2000*, Council's development consent and to maintain reasonable levels of public health and environmental amenity.

Use of Premises

57. The premises must only be used as a single residential dwelling and must not be used for dual or multi-occupancy purposes.

External Lighting

58. External lighting to the premises must be designed and located so as to minimise light-spill beyond the property boundary or cause a public nuisance.

Plant & Equipment

59. Noise from the operation of all plant and equipment upon the premises shall not give rise to an 'offensive noise' as defined in the *Protection of the Environment Operations Act 1997 and Regulations*.

In this regard, the operation of the plant and equipment shall not give rise to an $L_{Aeq, 15 \text{ min}}$ sound pressure level at any affected premises that exceeds the background $L_{A90, 15 \text{ min}}$ noise level, measured in the absence of the noise source/s under consideration by more than 5dB(A) in accordance with relevant NSW Office of Environment & Heritage (EPA) Noise Control Guidelines.

Swimming/Spa Pools

60. The pool plant and equipment shall not be operated during the following hours if the noise emitted can be heard within a habitable room in any other residential premises, or, as otherwise specified in relevant Noise Control Regulations:

- before 8.00am or after 8.00pm on any Sunday or public holiday; or
- before 7.00am or after 8.00pm on any other day.

Air Conditioners

61. Air conditioning plant and equipment shall not be operated during the following hours if the noise emitted can be heard within a habitable room in any other residential premises, or, as otherwise specified in relevant Noise Control Regulations:

- before 8.00am or after 10.00pm on any Saturday, Sunday or public holiday; or
- before 7.00am or after 10.00pm on any other day.

Rainwater Tanks

62. The operation of plant and equipment associated with rainwater tanks are to be restricted to the following hours if the noise emitted can be heard within a habitable room in any other residential premises:

- before 8.00am or after 8.00pm on weekends or public holiday; or
- before 7.00am or after 8.00pm on weekdays.

ADVISORY NOTES

The following information is provided for your assistance to ensure compliance with the *Environmental Planning & Assessment Act 1979*, *Environmental Planning & Assessment Regulation 2000*, or other relevant legislation and Council's policies. This information does not form part of the conditions of development consent pursuant to Section 4.17 of the Act.

A1 The requirements and provisions of the *Environmental Planning & Assessment Act 1979* and *Environmental Planning & Assessment Regulation 2000*, must be fully complied with at all times.

Failure to comply with these requirements is an offence, which renders the responsible person liable to a maximum penalty of \$1.1 million. Alternatively, Council may issue a penalty infringement notice (for up to \$3,000) for each offence. Council may also issue notices and orders to demolish unauthorised or non-complying building work, or to comply with the requirements of Council's development consent.

A1 This determination does not include an assessment of the proposed works under the Building Code of Australia (BCA) and other relevant Standards. All new building work (including alterations and additions) must comply with the BCA and relevant Standards and you are advised to liaise with your architect, engineer and building consultant prior to lodgement of your construction certificate.

A2 In accordance with the requirements of the *Environmental Planning & Assessment Act 1979*, building works, including associated demolition and excavation works (as applicable) must not be commenced until:

- A *Construction Certificate* has been obtained from an Accredited Certifier or Council,
- An Accredited Certifier or Council has been appointed as the *Principal Certifying Authority* for the development,
- Council and the Principal Certifying Authority have been given at least 2 days notice (in writing) prior to commencing any works.

A3 Council can issue your *Construction Certificate* and be your *Principal Certifying Authority* for the development, to undertake inspections and ensure compliance with the development consent and relevant building regulations. For further details contact Council on 9093 6944.

A4 A Local Approval application must be submitted to and be approved by Council prior to commencing any of the following activities on a footpath, road, nature strip or in any public place:

- Install or erect any site fencing, hoardings or site structures
- Operate a crane or hoist goods or materials over a footpath or road
- Placement of a waste skip or any other container or article.

For further information please contact Council on 9093 6971.

A5 Specific details of the location of the building/s should be provided in the Construction Certificate to demonstrate that the proposed building work will not encroach onto the adjoining properties, Council's road reserve or any public place.

A6 Prior to commencing any works, the owner/builder should contact *Dial Before You Dig* on 1100 or www.dialbeforeyoudig.com.au and relevant Service Authorities, for information on potential underground pipes and cables within the vicinity of the development site.

A7 This consent does not authorise any trespass or encroachment upon any adjoining or supported land or building whether private or public. Where any underpinning, shoring, soil anchoring (temporary or permanent) or the like is proposed to be carried out upon any adjoining or supported land, the land owner or principal contractor must obtain:

- the consent of the owners of such adjoining or supported land to trespass or encroach, or
- an access order under the *Access to Neighbouring Land Act 2000*, or
- an easement under section 88K of the *Conveyancing Act 1919*, or
- an easement under section 40 of the *Land & Environment Court Act 1979*, as appropriate.

Section 177 of the *Conveyancing Act 1919* creates a statutory duty of care in relation to support of land. Accordingly, a person has a duty of care not to do anything on or in relation to land being developed (the supporting land) that removes the support provided by the supporting land to any other adjoining land (the supported land).

- A8 Council's assessment of this application does not include an assessment of compliance with the *Swimming Pool Act 1992*. All pool barriers, fences and structures within properties containing a swimming pool must comply with the requirements of the *Swimming Pool Act 1992*, BCA and relevant Australian Standards.

Details of compliance with the *Swimming Pool Act 1992*, Building Code of Australia and relevant Standards must be included in the Construction Certificate to the satisfaction of the Certifying Authority.

- A9 Underground assets (eg pipes, cables etc) may exist in the area that is subject to your application. In the interests of health and safety and in order to protect damage to third party assets please contact Dial before you dig at www.1100.com.au or telephone on 1100 before excavating or erecting structures (This is the law in NSW). If alterations are required to the configuration, size, form or design of the development upon contacting the Dial before You Dig service, an amendment to the development consent (or a new development application) may be necessary. Individuals owe asset owners a duty of care that must be observed when working in the vicinity of plant or assets. It is the individual's responsibility to anticipate and request the nominal location of plant or assets on the relevant property via contacting the Dial before you dig service in advance of any construction or planning activities.
- A10 The applicant is to advise Council in writing and/or photographs of any signs of existing damage to the Council roadway, footway, or verge prior to the commencement of any building/demolition works.
- A11 Further information and details on Council's requirements for trees on development sites can be obtained from the recently adopted Tree Technical Manual, which can be downloaded from Council's website at the following link, <http://www.randwick.nsw.gov.au> - Looking after our environment – Trees – Tree Management Technical Manual; which aims to achieve consistency of approach and compliance with appropriate standards and best practice guidelines.